

### TITAN Injection Anchor 52 / 26

<b>01 TITAN Injection Anchor 52/26</b> , ultimate load 925 kN, yield point 730 kN, acc. to EN 10210-1 S460, continuously <b>right hand</b> threaded in lengths of <b>3 m</b> , packing unit 50 pcs.,		
<b>black</b> .....	<b>art.no. 03308510</b>	9,87 kg/m
<b>hot-galvanized</b> .....	<b>art.no. 03308610</b>	10,50 kg/m
<b>duplex-coated = hot-dip galv. and epoxy coated</b>		
<b>art.no. 03308517</b> .....		10,06 kg/m

cutting of Injection Anchor 52/26



### Accessories

<b>02 Coupling Nut, Ø 70 x 160 mm</b> , with center-stop, hardened, with 2 rubber seals, packing unit 500 pcs. / wire-mesh pallet		
<b>black</b> .....	<b>art.no. 01308560</b>	2,36 kg
<b>hot-galvanized</b> .....	<b>art.no. 01308660</b>	2,39 kg



<b>03 Spherical Collar Nut SW 80 x 70 mm</b> , max. inclination $\pm 10^\circ$ of washer plate,		
<b>black</b> .....	<b>art.no. 03308551</b>	2,20 kg
<b>hot-galvanized</b> .....	<b>art.no. 03308651</b>	2,24 kg



<b>04 Washer Plate, 220 x 220 x 35 mm</b> for anchorpiles, hole $\varnothing$ 65 mm,		
<b>black</b> .....	<b>art.no. 03308547</b>	12,10 kg
<b>hot-galvanized</b> .....	<b>art.no. 03308548</b>	13,20 kg

<b>05 Washer Plate, 145 x 145 x 28 mm</b> for anchorpiles, hole $\varnothing$ 65 mm		
<b>black</b> .....	<b>art.no. 01308563</b>	3,73 kg
<b>hot-galvanized</b> .....	<b>art.no. 01308564</b>	3,73 kg



<b>06 Protection Cap, Ø 193,7 mm</b> , 146 mm high, steel, for permanent anchor piles,		
<b>art.no. 03307643</b> .....		4,60 kg



<b>07 Steel Ball Ø 110 mm</b> , for HD-PE tube $\varnothing$ 63 mm, max. inclination $\pm 45^\circ$ , <b>black</b> ,		
<b>art.no. 01308525</b> .....		3,80 kg



<b>08 Plate for steel ball Ø 110 mm, 230 x 230 x 50 mm</b> , max. inclination $45^\circ$ , without steel ball, <b>black</b> ,		
<b>art.no. 01308526</b> .....		14,70 kg



<b>09 Wedge Disc, 12°</b> , allows max. 2 x 12°, <b>black</b> ,		
<b>art.no. 01308593</b> .....		5,00 kg




<b>10 Bayonet Coupler with plate, Ø 220 x 35 mm</b> , to resist uplift		
<b>art.no. 06308525</b> .....		11,65 kg



<b>11 Bayonet Connector for drilling through soil</b> , reusable 20 to 50 times,		
<b>art.no. 06308524</b> .....		2,80 kg



<b>12 Bayonet Coupler for drilling through soil</b> ,		
<b>art.no. 06308523</b> .....		2,33 kg



### Accessories

13 - 15




13 HD-PE Tube, Ø 63 x 3,6 x 3000 mm, packing unit 50 pcs. in a bundle art.no. 07308545.....	2,10 kg
---	---------

14 HD-PE Tube, Ø 140 x 8,0 x 3000 mm, art.no. 07307746.....	10,00 kg
--	----------

15 HD-PE Tube, Ø 110 x 3,4 x 3000 mm, art.no. 06307747.....	4,00 kg
--	---------

16 - 18



16 TITAN Hardened Clay Bit, Ø 130 mm art.no. 01308554.....	2,37 kg
---	---------

17 TITAN Hardened Clay Bit, Ø 175 mm art.no. 01308546.....	2,60 kg
---	---------

18 HPI-Clay Bit, Ø 130 mm for jetgrouting with 1 carbide-nozzle, Ø 3,5 mm, art.no. 01308553.....	2,40 kg
--	---------

19 - 20



19 TITAN Cross Cut Drill Bit, Ø 115 mm, hardened, for mixed soil with obstacles art.no. 06308565.....	1,92 kg
--	---------

20 TITAN Cross Cut Drill Bit, Ø 130 mm, hardened, for mixed soil with obstacles art.no. 01308535.....	2,90 kg
--	---------



21 TITAN Carbide Cross Cut Drill Bit, Ø 115 mm for TITAN 52/26, art.no. 06308536.....	3,30 kg
--	---------

22



22 TITAN Carbide Button Drill Bit, Ø 115 mm, for hard or high quartzite rock, art.no. 06308564.....	3,50 kg
--	---------



23 Centralizer Ø 112 mm, cast iron, black, art.no. 01308595.....	1,20 kg
---	---------

24





24 Adapter for Injection Anchor 52/26 to drill bit 73/53, right hand, art.no. 06308578.....	1,30 kg
---	---------

25



25 Tensioning + Measuring Kit 600 kN capacity, comprising of hollow hydraulic jack with 220 V electric pump, tensioning chair, extension anchor piece with coupler, INOX spherical collar nut, dial gauge with holder and plate, art.no. 06308515.....	160,00 kg
---	-----------



### TITAN Injection Anchor 52 / 26 + Accessories

<b>01 TITAN Injection Anchor 52/26</b> , ultimate load 925 kN, yield point 730 kN, acc. to EN 10210-1 S460, continuously <b>left hand</b> threaded in lengths of 3 m, packing unit 50 pcs.,		
<b>black</b> .....	<b>art.no. 03308710</b>	9,87 kg/m
<b>hot-galvanized</b> .....		10,50 kg/m
<b>duplex-coated</b> = hot-dip galv. and epoxy coated		10,06 kg/m

cutting of Injection Anchor 52/26

### Accessories



<b>02 Coupling Nut</b> , Ø 70 x 160 mm, with center-stop, hardened, with 2 rubber seals, <b>left hand thread</b> , packing unit 500 pcs. / wire-mesh pallet		
<b>black</b> .....	<b>art.no. 01308760</b> .....	2,36 kg
<b>galvanized</b> .....	<b>art.no. 01308761</b> .....	2,39 kg



<b>03 Spherical Collar Nut</b> SW 80 x 70 mm, max. inclination ± 10° of washer plate, <b>left hand thread</b>		
<b>black</b> .....	<b>art.no. 03308751</b> .....	2,20 kg
<b>galvanized</b> .....	<b>art.no. 03308752</b> .....	2,24 kg



<b>04 Bayonet Coupler with Plate</b> Ø 220 x 35 mm, to resist uplift, <b>left hand thread</b> , bayonet connector required		
<b>art.no. 06308725</b> .....		11,65 kg



<b>05 Bayonet Connector</b> , for drilling through soil, reusable 20 to 50 times, <b>left hand thread</b>		
<b>art.no. 06308724</b> .....		2,80 kg



<b>06 Bayonet Coupler</b> for drilling through soil, <b>left hand thread</b>		
<b>art.no. 06308723</b> .....		2,20 kg



<b>07 TITAN Hardened Clay Bit</b> , Ø 130 mm, <b>left hand thread</b> ,		
<b>art.no. 01308754</b> .....		2,43 kg

<b>08 TITAN Hardened Clay Bit</b> , Ø 175 mm, <b>left hand thread</b> ,		
<b>art.no. 01308746</b> .....		2,60 kg

<b>09 TITAN HPI-Clay Bit</b> , Ø 130 mm, for jetgrouting with 1 carbide-nozzle, Ø 3,5 mm, <b>left hand thread</b>		
<b>art.no. 01308753</b> .....		2,40 kg



<b>10 TITAN Cross Cut Drill Bit</b> , Ø 115 mm, hardened, for mixed soils with obstacles, <b>left hand thread</b>		
<b>art.no. 01308735</b> .....		1,92 kg

<b>11 TITAN Cross Cut Drill Bit</b> , Ø 130 mm, hardened, for mixed soils with obstacles, <b>left hand thread</b> ,		
<b>art.no. 01308736</b> .....		2,90 kg



<b>12 TITAN Carbide Button Drill Bit</b> , Ø 115 mm, <b>left hand thread</b>		
<b>art.no. 06308764</b> .....		5,98 kg

Washer plate, threaded headplate, steel ball, wedge disc and Injection Anchors in hot-galvanized and duplex-coated see price list 52/26-1 with right hand thread.